

PRO M8

CARACTERÍSTICAS



8 PULGADAS

- 110~240VAC, 50/60HZ
- BATERÍA INTEGRADA (2 HRS CONTINUAS)
- TEMPERATURA: 2 CANALES
- SPO2: 0~100% , PRECISIÓN: 70-100%: +/- 2%, RESOLUCIÓN 1%
- NIBP: OSCILOMETRICO: ADULTO: 10~280, PED: 10~220, NEO: 10~130 MMHG
- RESPIRACIÓN: ADULT: 0~120 RPM, NEO: 0~150 RPM
- ECG: 5 DERIVACIONES, LEAD SELECON: I, II, III, VR, AVL, AVF, V /OR I, II, III
- GAIN: AUTO, 2.5, 5, 10, 20MM/MV
- HR RANGE: ADULT: 15-300BPM; PED/NEO: 15-350BPM
- HR ACCURACY: $\pm 1\%$ OR ± 1 BPM HR RESOLUON: 1BPM

ACCESORIOS ESTANDAR



ECG Cable



NIBP Cuff



SPO2 Sensor



TEMP Probe

PRO M12

CARACTERÍSTICAS

12 PULGADAS

- 110~240VAC, 50/60HZ
- BATERÍA INTEGRADA (2 HRS CONTINUAS)
- TEMPERATURA: 2 CANALES
- SPO2: 0~100% , PRECISIÓN: 70-100%: +/- 2%, RESOLUCIÓN 1%
- NIBP: OSCILOMETRICO: ADULTO: 10~280, PED: 10~220, NEO: 10~130 MMHG
- RESPIRACIÓN: ADULT: 0~120 RPM, NEO: 0~150 RPM
- ECG: 5 DERIVACIONES, LEAD SELECON: I, II, III, VR, AVL, AVF, V /OR I, II, III
- GAIN: AUTO, 2.5, 5, 10, 20MM/MV
- HR RANGE: ADULT: 15-300BPM; PED/NEO: 15-350BPM
- HR ACCURACY: $\pm 1\%$ OR ± 1 BPM HR RESOLUON: 1BPM



Distribuidor

Beracah
MEDICA

ventas@beracahmedica.mx

662 15 10 979



PRO M15

CARACTERÍSTICAS

- 110~240VAC, 50/60HZ
- BATERÍA INTEGRADA (2 HRS CONNUAS)
 - TEMPERATURA: 2 CANALES
 - SPO2: 0~100% ,
 - PRECISIÓN: 70-100%: +/- 2%, R
 - RESOLUCIÓN 1%
 - NIBP: OSCILOMETRICO: ADULTO: 10~280, PED: 10~220, NEO: 10~130 MMHG
 - RESPIRACIÓN: ADULT: 0~120 RPM, NEO: 0~150 RPM
 - ECG: 5 DERIVACIONES, LEAD SELECON: I, II, III, VR, AVL, AVF, V /OR I, II, III
 - GAIN: AUTO, 2.5, 5, 10, 20MM/MV
 - HR RANGE: ADULT: 15-300BPM; PED/NEO: 15-350BPM
 - HR ACCURACY: $\pm 1\%$ OR ± 1 BPM HR RESOLUON: 1BPM

ACCESORIOS



DISTRIBUIDO POR: