

Maximum Performance





UY350, UY450, UY600

FEATURES AND BENEFITS

- Freestanding, high spin
- Stainless steel cabinet
- Stainless steel drum and tub
- PROform fully programmable microprocessor
- Large door opening for easy loading and unloading (Ø 540 mm)
- Two large drain valves (Ø 76 mm)
- Frequency controlled motor
- Perforated lifting ribs: more mechanical action, lower water consumption
- Ecological washing programmes significantly reduces water and electricity consumption
- USB and RS485 plug (on the back panel)
- Liquid soaps print
- Soap hopper with 5 removable compartments
- 3rd water inlet, high inlets capacity
- Ergonomic height of door enables easy access with trolleys
- · User friendly control position regardless user's height
- Bumper (front side protection)

OPTIONS

- Liquid soap pumps
- PROform Assist traceability software and networking system
- Weighing system by cells
- Recycle drain valve
- Isolation for energy and noise reduction
- Extra signalization (orange light + horn)
- Steam heating version
- Air operated water inlets
- Water sample tap

TYPE		UY350	UY450	UY600
INNERDRUM				
Capacity (1:10)	kg/lb	35/77	45/99	60/132
Volume	l	350	450	600
Diameter	mm	914	914	1035
Depth	mm	535	690	715
MOTOR				
Power	kW	4	7,5	7,5
DRUM SPEED				
Wash speed (max)	rpm	45	45	42
Extraction speed (max)	rpm	839	839	788
G-Factor		360	360	360
PROGRAMMER				
PROform		Standard	Standard	Standard
HEATING				
100% hot water	°C	90	90	90
100% electrical	kW	24	36	54
Steam high pressure	bar	3-8	3-8	3-8
CONNECTION				
Electrical			3x220-240V 50/60Hz 3x380-415V 50/60Hz 3x440-480V 50/60Hz	
Water inlet	inch	3x 1 "	3x 1 "	3x 1 "
Steam inlet	inch	1x 3/4"	1x 3/4"	1x 3/4"
Drain diameter	inch	2x 3 "	2x 3 ″	2x 3 "
TILTING				
Forward tilting		N/A	Option	Option
DIMENSIONS				
HxWxD	mm	1925x1315x1270	1925x1315x1502	1925x1315x1502
TRANSPORT DATA				
Net weight	kg	1010	1350	1500
Net weight (w/ tilting)	kg	N/A	1390	1540
Gross weight	kg	1170	1490	1640
Gross weight (w/ tilting)	kg	N/A	1530	1680
Crate packing HxWxD	mm	2125x1425x1470	2125x1425x1700	2125x1425x1700
Standard = Standard version. The data concerning dimensions	of machines include a	l extended parts.		

